

# eco M



Carry: Waist/ hip belt



## Always at hand - never in the way!

Available with 12, 16 or 24 operational commands. Suitable for hydraulic loading cranes with 4 or 6 proportional functions. With key switch and HBC joysticks with up to 4 steps mounted in a metal housing for safe operation even while wearing work gloves. With STOP push button, also suitable for safe shutdown of machinery.



Rotary frequency switch for easy channel changing in connection with the patented HBC-Automatic-Frequency-Scanner mounted in the receiver. The ergonomically designed rollover bar combines non-tiring operation with all safety requirements.



Additional operations: Catch-Release (Pitch and Catch)/ Tandem Operation



# eco M

**Always at hand - never in the way!**

**Technical data:**

Commands: 12, 16, 24 or 8 + 4-6 proportional functions + STOP

Power supply: NiCd battery FuB 05 AA (rechargeable), operating time approx. 12 hours/ 100 %ON

Operating elements: 2 HBC joysticks in all metal design, up to 4-steps or stepless/  
up to 6 HBC push buttons (1-step)/ 2 toggle switches or rotary switches/  
STOP push button/ key switch (ON/ OFF)

Option: Automatic-Frequency-Scanner for industrial systems/  
Additional operations: Catch-Release (Pitch and Catch)/  
Tandem Operation/ available for Ex-Zone 2

Transmitter weight: Approx. 1,5 kg/ 3.3 lb. (battery included)

Transmitter dimensions: 216 x 112 x 176 mm/ 8.5 x 4.4 x 6.9 " (LxWxD)

Suitable receivers: FSE 716, FSE 722, FSE 735 radiobus®



**System includes:**

- 1 receiver with antenna and multi-pin-plug
- 2 rechargeable batteries
- 1 smart battery charger (combats memory effect), charging process approx. 4 hours.
- 1 carrying belt
- 1 set operating instructions

**Neck or shoulder strap**



**Special versions on request.**



**Change the transmitter battery within seconds.**

